



Dry Block Temperature Calibrator

Model No. ED-27X

Range : -30°C to 100°C @ 25°C



**Easy to Carry,
Portable
Ergonomic
Design**

**High Precision
Best in class
Thermal Stability &
Uniformity**

**Calibration of
thermometers,
temperature sensors,
temperature
indicators**

Features

1. Temperature range -30 °C to 100 °C @ 25 °C.
2. Light weight, Rugged, Fast cooling to deep freezing range.
3. No bulky compressor.
4. Best In class product for Calibration of temperature sensor, Thermometers, Transmitters.
5. No Bulky compressor.



Dry Block Temperature Calibrator

Model No. ED-27X

Technical Specification

1. Temperature Range: -30 °C to +100 °C @ 25 °C ambient temperature.
2. Control accuracy: ± 0.05 °C Below Ambient temperature.
3. Control accuracy: ± 0.1 °C Above Ambient temperature.
4. Thermal stability:
 - ± 0.01 °C @100 °C (calculated after stabilization time of 10 minutes).
 - ± 0.01 °C @ - 30°C (calculated after stabilization time of 10 minutes).
5. Thermal Nonuniformity (Radial):
 - ± 0.15 °C @100 °C (calculated after stabilization time of 10 minutes).
 - ± 0.10 °C @-30°C (calculated after stabilization time of 10 minutes).
6. Stabilization Time/settling time: 10 minutes after set point is achieved .
7. Time to reach -30 °C (15 Minutes) from 25 °C ambient temperature .
8. Power supply: 100-240 VAC @50-60 Hz.
9. Current : 0.7 A.
10. Power Consumption: single phase , 170 Watt maximum.
11. Sound: 30 dB.
12. Enclosure Metal(SS).

Storage Condition

1. Temperature: 0 °C - 40 °C.
2. Relative Humidity: 30 % RH -85 % RH .
3. Fuse rating :3 A.
4. Non Condensing

Accessories

1. Carry bag.
2. Pointer puller
3. Operating manual.
4. 17025 Accredited Calibration certificate: Optional
5. Costomised Insert: Optional

Caters
to large
calibration work
load from Deep freez-
ing temperature
range to
100 °C



Dry Block Temperature Calibrator

Model No. ED-27X

Dimensions



Insert Dimensions

