

Dew CAL

Premium Accuracy Dew Point Hygro-Meter

Model No: DEWP-01B



Dew Point

Temperature RH

unix

Premium Accuracy Dew Point Hygro-Meter

Model No: DEWP-01B

Special Features

- 1) Premium best in class accuracy Dew point Meter with thermo-hygrometer proficient for high accuracy metrological applications, testing and calibration labs, R & D Applications,
- 2) Hand held enclosure with silicon rubber protecter.
- 3) Long sensor cable length usefull for taking mesurements in ducts, chambers, cleanrooms, Protected enclosures
- 4) Minimum maximum function with reset feature
- 5)Protection class IP40, flame resistant ABS UL94V-0 Enclosure.

Technical Specification

1) Measurement Range (Sensor only)

Dew point range - upto -40 deg c (barometric/ambient pressure)

Temperature: -40 °C. to 60 °C.

Relative Humidity: 0 % RH to 100% RH.

2) Accuracy: ± 0.1 deg c Dp

 $\pm 0.8 \% RH$

 $\pm 0.3 \, ^{\circ}\text{C} \, (@ \, 23 \, ^{\circ}\text{C})$

3) Resolution: 0.01 Dp/ 0.01 °C/ 0.01% RH

4) Repeatability: $\pm 0.2 \%$ RH/ $\pm 0.15 °$ C.

- 5) Sensor probe length: 175mm, Probe Dia: 15mm
- 6) Sensor cable length: 1.5 meters
- 7) Power supply: 2 AA dry batteries, User replacable.
- 8) Battery Back up: 2 Hrs continuous use with backlight on.
- 9) Dimensions: 150mm (L) X 100mm(B) X 35mm (W)
- 10) Weight: 410 g.

Environmental conditions of use

Applicable for measurement/ Readout unit only

Temperature: 0 °C. to 50 °C.

Relative Humidity: 0 % RH to 80 % RH.

Satandard Accessories

- 1) Operating manual With Warranty certificate and general factory Calibration Certificate.
- 2) 17025 Accredited Calibration Certificate (optional).
- 3) Carry bag (optional)

